






Features

- Ultra High Resolution: 540 TV lines
- Wide Dynamic Range
- $f=3.7\text{mm}$ pinhole lens
- Minimum illumination: 0.8 Lux / F1.2
- 32x Sense up
- OSD Menu

Dimensions

Unit: mm



Specifications

MODEL	SF039M
PICK UP DEVICE	1/3" Pixim DPS Sensor
TOTAL PIXELS	720 (H) x 540 (V)
HORIZONTAL RESOLUTION	540 TVL
LENS	3.7mm pinhole lens
VIEW ANGLE (HORIZONTAL)	66°
MIN. ILLUMINATION	0.8 Lux / F1.2
ELECTRONIC SHUTTER	PAL: 1/50 ~ 1 / 100,000 sec NTSC: 1/60 ~ 1 / 100,000 sec
ELECTRONIC SHUTTER CONTROL	Built-in
WIDE DYNAMIC RANGE	Yes
BACK LIGHT COMPENSATION	On / Off selectable
S / N RATIO	More than 50dB (AGC off)
WHITE BALANCE	ATW / AWB / Manual
VIDEO OUTPUT CONNECTOR	1.0 Vp-p, 75Ω
AUTO GAIN CONTROL	Low / Medium / High / Custom
OSD MENU	English
NOISE REDUCTION	Auto
POWER SOURCE	12V DC / 24V AC
OPERATING TEMPERATURE	-10°C ~ 50°C
HUMIDITY	<90%
NET WEIGHT (G)	140
DIMENSION	42(L) x 42.3 (W) x 54 (H) mm

www.TeleEye.com

TeleEye Group

China Croatia Hong Kong Macau Mauritius
Philippines Singapore South Africa Sri Lanka U.K.

DISTRIBUTED BY: